



## WFM 14000-MTHE

Reference: 09243

### BOXER P Series

Generating sets with original HONDA twin-cylinder petrol engine in a sturdy semi-casing frame with power from 10 to 12 KVA, single-phase or three-phase/single-phase, 3000 rpm, air cooling, key start including battery and electrical panel with sockets and protection as standard. Can be combined with various accessories for professional use and use in the event of a blackout.

Complete with a 20-litre tank for long operating autonomy.

Not intended for outdoor use.

Noise level does not comply with Directive 2000/14/EC.

#### Main features:

- protective frame with semi-enveloping upper hood
- original Honda engine compliant with low CO2 emissions
- low oil level protection
- silencer
- primary Italian brand alternator
- oversized 20-litre petrol tank for long operating autonomy
- electric start with 12V battery supplied with acid
- full load test with test certificate
- user manual compliant with safety standards

The images are purely indicative.

### Technical Sheet

| Phase                            | Single phase / Three phase                |
|----------------------------------|---|
| Maximum power single phase (KW)  | 3.2                                       |
| Maximum power single phase (KVA) | 4   |
| Maximum power three phase (KW)   | 9.6                                       |
| Maximum power three phase (KVA)  | 12  |
| Fuel                             | Gasoline                                  |
| Frequency (Hz)                   | 50  |
| Voltage (V)                      | 230 / 400                                 |
| Sockets configuration            | 1 x 230V 16A 3P CEE - 1 x 230V 32A 3P CEE |

|                                    |                          |
|------------------------------------|--------------------------|
| Engine                             | Honda GX690R             |
| Engine rpm (rpm)                   | 3000                     |
| Starting system                    | Electric                 |
| Engine capacity (cm <sup>3</sup> ) | 688                      |
| Number cylinders                   | 2                        |
| Oil capacity (L)                   | 1.9                      |
| Cooling                            | Air                      |
| Fuel tank capacity (L)             | 20                       |
| Consumption (L/h)                  | 4.6 at 100% of the load  |
| Running time (h)                   | 4.34 at 100% of the load |
| Acoustic power                     | 100 dB(A)                |
| Acoustic pressure                  | 75 dB(A) at 7 m          |
| Length (mm)                        | 990                      |
| Width (mm)                         | 550                      |
| Height (mm)                        | 670                      |
| Dry weight (Kg)                    | 140                      |
| Silenced                           | No                       |
| Super silenced                     | No                       |
| ATS Switch device                  | Optional ATS             |
| Voltage regulator                  | No                       |
| Engine manufacturer                | Honda                    |