



WFM SE12000-MTHE AVR

Reference: 09317

Technical Sheet

| | |
|------------------------------------|---|
| Phase | Single phase / Three phase |
| Maximum power single phase (KW) | 3.2 |
| Maximum power single phase (KVA) | 4 |
| Maximum power three phase (KW) | 9.6 |
| Maximum power three phase (KVA) | 12 |
| Fuel | Gasoline |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Sockets configuration | 1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE |
| Engine | Honda GX690R |
| Engine rpm (rpm) | 3000 |
| Starting system | Electric |
| Engine capacity (cm ³) | 688 |
| Number cylinders | 2 |
| Oil capacity (L) | 1.9 |
| Cooling | Air |
| Fuel tank capacity (L) | 20 |
| Consumption (L/h) | 4.6 at 100% of the load |
| Running time (h) | 4.34 at 100% of the load |
| Acoustic power | 92 dB(A) |
| Acoustic pressure | 67 dB(A) at 7 m |

| | |
|---------------------|--------------|
| Length (mm) | 1070 |
| Width (mm) | 563 |
| Height (mm) | 921 |
| Dry weight (Kg) | 210 |
| Silenced | Yes |
| Super silenced | Yes |
| ATS Switch device | Optional ATS |
| Voltage regulator | No |
| Engine manufacturer | Honda |