

WFM SE12000-MTHE AVR

Reference: 09850



Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	13.3
Continuous power single phase (KW)	18
Maximum power single phase (KVA)	16
Continuous power single phase (KVA)	22.5
Maximum power three phase (KW)	40
Continuous power three phase (KW)	36
Maximum power three phase (KVA)	50
Continuous power three phase (KVA)	45
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	PERKINS 1103A-33TG1, aspirazione sovralimentata
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	3300
Number cylinders	3
Cooling	Water
Alternator	Leroy Somer LSA43.2 S25, brushless
Poles	4

Bore x stroke (mm)	105 x 127
Fuel tank capacity (L)	135
Consumption (L/h)	9 at 100% of the load
Running time (h)	15 at 100% of the load
Acoustic pressure	67 dB(A) at 7 m
Length (mm)	1940
Width (mm)	1000
Height (mm)	1480
Dry weight (Kg)	1200
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Perkins