



WFM TD-8000IM Metal Halide Lighting Tower with 8.8 kVA Genset

Reference: 06039

Key features of the WFM TD-8000IM lighting tower

- Lighting tower hydraulic 9 mt.
- Mast rotation 360°
- 4 1000W metal halide floodlights
- Genset and alternator of leading brands
- Tank 140 lt., operating time 85 hours
- Noise 65 dbA at 7 meters.
- Stabilizer feet and parking brake for a high level of operational safety
- Full load test with test certificate
- User's manual in compliance with safety regulations

Le immagini sono puramente indicative.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7
Maximum power single phase (KVA)	8.8
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 32A
Engine	Perkins 403D-1163
Starting system	Electric
Engine capacity (cm ³)	1131
Number cylinders	3
Oil capacity (L)	6
Type of lamps	Metal halide
Lamps	4 x 1000 W

Telescopic pole	Galvanized steel
Total lumens (Lm)	80000
Lifting System	Hydraulic lifting system
Maximum height (m)	9
Mast rotation	360°
Open size (mm)	2450 x 2800 x 9200
Length closed (mm)	2450
Width closed (mm)	1300
Height closed (mm)	2300
Transportability	Fast Trailer
Fuel tank capacity (L)	140
Consumption (L/h)	1.64 at 100% of the load
Running time (h)	85 at 100% of the load
Acoustic power	90 dB(A)
Acoustic pressure	65 dB(A) at 7 m
Dry weight (Kg)	1030