



## GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

Reference: MG 8000 BS/HA

### GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

GENSET MG 8000 BS/HA Single-phase generating set with Honda GX 390 OHV STAGE V engine powered by gasoline, capable of delivering a maximum power of 7 KVA complete with AVR voltage regulator.

The GENSET MG 8000 BS/HA generator set is compact and easy to use, equipped with a casing that lowers noise emissions and makes it super-silenced.

The GENSET MG 8000 BS/HA is equipped with electric start with 12 V battery and low fuel consumption, in fact it consumes only 3.3 liters/hour at 75% load.

The generator set GENSET MG 8000 BS/HA is part of the silenced series and are characterized by lower consumption and a longer life expectancy than the range powered by gasoline and equipped with soundproof cabin suitable for installation and outdoor use, and increased tank. The GENSET MG 8000 BS/HA generator set at 3000 rpm is suitable for emergency use only. It is not recommended to use it for more than 6 continuous hours and for more than 500 hours per year.

#### TECHNICAL FEATURES GENSET MG 8000 BS/HA

Phase Type: Single-Phase  
Maximum Single-Phase Power: 7 KVA / 5.6 KW  
VAC Voltage: 230 / 400 V  
Frequency (Hz): 50  
Quadro Starter: Manual with self-winding  
Motor: Honda GX 390 OHV  
Emission Standard: STAGEV  
RPM: 3000  
Power supply: Gasoline  
Fuel tank capacity: 10.5 l  
Consumption @ 75 % load: 3.3 l/h  
Autonomy @ 75 % load: 3.18 h  
Sound pressure: 86 dB(A)  
Length: 1059 mm  
Width: 670 mm  
Height: 740 mm  
Net weight: 138 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the full range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	5.6
Maximum power single phase (KVA)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A CEE - 1 x 230V 32A CEE
Engine	Honda GX390, 4 stroke, OHV
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	390
Number cylinders	1
Cooling	Air
Alternator	Synchronous
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	10.5
Consumption (L/h)	3.3
Running time (h)	3.18
Acoustic power	86 dB(A)
Acoustic pressure	61 dB(A) at 7 m
Length (mm)	1059
Width (mm)	670
Height (mm)	740
Dry weight (Kg)	138
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR

---

Engine manufacturer

Honda

---