



GENSET MG 10/6 S-R - SINGLE-PHASE/THREE-PHASE GENERATOR 10 KVA

Reference: MG 10/6 S-R - COMP

GENSET MG 10/6 S-R SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

GENSET MG 10/6 S-R Singlephase / threephase generating set with Lombardini 25LD330/2 diesel engine, capable of delivering a maximum power of 10KVA with AVR **Optional** voltage regulator.

The GENSET MG 10/6 S-R generator set is compact and easy to use, equipped with enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 10/6 S-R is a 10 KVA singlephase/threephase diesel generator set with electric start. This generator is also available in the version with AVR voltage regulator, with automatic panel and remote control.

Thanks to its compact size and very low weight, the GENSET MG 10/6 S-R is a lightweight generator that is easy to transport. The GENSET MG 10/6 S-R also has a low fuel consumption: only 2.2 Lt/h at 75% load.

The GENSET MG 10/6 S-R generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The generating GENSET MG 10/6 S-R includes:

- Voltmeter
- Hour meter
- Differential magnetothermal switch
- Emergency stop button
- Starting battery
- 1 threephase socket CEE 16A, 400V - 50 Hz
- 1 singlephase socket CEE 32A, 230V - 50 Hz
- 1 singlephase socket CEE 16A, 230V - 50 Hz
- Protection for power outputs
- Arrangement for operation in AMF/ATS or remote control
- Voltmetric switch
- Central lifting hook

TECHNICAL FEATURES GENSET MG 10/6 S-R

Phase Type: SinglePhase / ThreePhase
Maximum SinglePhase Power: 8.3 KVA / 6.64 KW
Maximum ThreePhase Power: 10 KVA / 8 KW
VAC Voltage: 230 / 400 V
Frequency (Hz): 50
Starting Frame: Electric

Engine: Lombardini 25LD330/2
 Emission Regulations: Non-emitting
 RPM: 3000
 Power supply: Diesel
 Fuel tank capacity: 10.5 l
 Consumption @ 75 % load: 2.2 l/h
 Autonomy @ 75 % load: 4.77 h
 Sound pressure: 97 dB(A)
 Length: 1000 mm
 Width: 560 mm
 Height: 730 mm
 Net weight: 190 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	6.64
Maximum power single phase (KVA)	8.3
Maximum power three phase (KW)	8
Maximum power three phase (KVA)	10
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A CEE - 1 x 230V 16A CEE - 1 x 230V 32A CEE
Engine	Lombardini 25LD330.2, 4 stroke
Emissions Regulations	Stationary Use
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	654
Number cylinders	2
Cooling	Air
Alternator	Synchronous
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	10.5
Consumption (L/h)	2.2
Running time (h)	4.77

Acoustic power	97 dB(A)
Acoustic pressure	72 dB(A) at 7 m
Length (mm)	1000
Width (mm)	560
Height (mm)	715
Dry weight (Kg)	190
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR (optional)
Engine manufacturer	Lombardini