



GENSET MG 10/8 SS-K - SINGLE-PHASE/THREE-PHASE GENERATOR 10 KVA

Reference: MG 10/8 SS-K

GENSET MG 10/8 SS-K SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

GENSET MG 10/8 SS-K is a singlephase / threephase generating equipped with a Kubota D722 (STAGE V) Diesel engine, capable of delivering a maximum power of 10KVA.

The GENSET MG 10/8 SS-K provides reliable power for home, business and recreational environments, safely powering appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop with clear, intuitive controls. The GENSET MG 10/8 SS-K is powered by a Kubota D722 **STAGE V** Diesel engine. These are very reliable engines that guarantee efficient combustion and low fuel consumption, and are also equipped with a protection system that causes the engine to stop if the oil level is too low.

The GENSET MG 10/8 SS-K has an all-steel construction and a large metal tank. The generator set guarantees an efficient and silent operation thanks to the Kubota D722 which allows to deliver a maximum power of 10 KVA.

The generator GENSET MG 10/8 SS-K comes with:

- Battery 12 V
- 1 threephase socket CEE 400V - 16A
- 1 singlephase socket CEE 230V - 32A
- 1 singlephase socket CEE 230V - 16A
- Thermal protection 16A
- Thermal protection
- Differential switch
- Emergency stop button
- Voltage selector
- Voltmeter
- Hour meter
- Central lifting hook
- Arrangement for operation in AMF-ATS or Remote control
- Glow plugs preheating warning light
- Automatic engine stop device with warning lights for:
 - battery failure
 - high water temperature
 - low oil pressure
 - low fuel level

TECHNICAL FEATURES GENSET MG 10/8 SS-K

Phase Type: SinglePhase/ThreePhase

Maximum SinglePhase Power: 6 KVA / 4.8 KW
 Maximum ThreePhase Power: 10 KVA / 8 KW
 VAC Voltage: 230 / 400 V
 Frequency (Hz): 50
 Quadro Starter: Electric
 Motor: Kubota D722
 Emission Standard: Stage V
 RPM: 3000
 Power supply: Diesel
 Fuel tank capacity: 30 l
 Consumption @ 75 % load: 3.3 l/h
 Autonomy @ 75 % load: 9.09 h
 Acoustic pressure: 95 dB(A)
 Length: 1360 mm
 Width: 675 mm
 Height: 860 mm
 Net weight: 350 Kg

Are you looking for a generator with different characteristics? [Here](#) you can find the full range of GENSET products or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	4.8
Maximum power single phase (KVA)	6
Maximum power three phase (KW)	8
Maximum power three phase (KVA)	10
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A CEE - 1 x 230V 16A CEE - 1 x 230V 32A CEE
Engine	KUBOTA D722, 4 stroke
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	719
Number cylinders	3
Cooling	Water
Alternator	Synchronous
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	30

Consumption (L/h)	3.3
Running time (h)	9.09
Acoustic power	90 dB(A)
Acoustic pressure	65 dB(A) at 7 m
Length (mm)	1360
Width (mm)	675
Height (mm)	860
Dry weight (Kg)	350
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	Compound
Engine manufacturer	Kubota