



MASE MARINER 1600 S SINGLE PHASE SILENCED MARINE GENERATOR 15.3 KW

Reference: 002962

MASE MARINER 1600 S SILENCED SINGLE-PHASE MARINE GENERATOR 15.3 KW

MASE MARINER1600S single phase silenced marine generator is equipped with a Yanmar 4TNV88 diesel engine capable of delivering a maximum power of 15.3 KW at 1500 rpm.

The MASE MARINER1600S is built with and synchronous alternator, self-excited with air cooling, it is extremely compact and powerful, suitable even on small boats.

The MASE MARINER1600S allows easy access for maintenance of the fuel and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high engine temperature or exhaust gas.

The alternator of the MASE MARINER1600S is synchronous with 4 poles, self-regulated, self-excited, brushless, which in conjunction with the powerful Yanmar engine can deliver a maximum power of 15.3 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current as the home.

The MASE MARINER1600S marine generator is equipped with a soundproof cabin that makes it super quiet, with a sound emission of 52 dB(A) at a distance of 7 m. The soundproof cabin in painted aluminum is extremely lightweight and of very high resistance to external agents.

TECHNICAL FEATURES MASE MARINER1600S

Phase Type: Single Phase
Maximum Output: 15.3 KW
Continuous Use Output: 13.9 KW
Fuel: Diesel
Voltage: 115 - 230 V
Frequency: 50 Hz
Motor: Yanmar 4TNV88, 4 Stroke
Mechanical Power: 24.5 Hp
Number of Cylinders: 4
Displacement: 2190 cc
RPM Regulator: Mechanical Centrifugal
Engine RPM: 1500 rpm
Fuel Consumption: 5.6 l/h
Sound pressure: 52 dB(A) @ 7 m
Alternator: Synchronous Brushless
Voltage regulator: AVR
Length: 1135 mm
Width: 631 mm

Height: 694 mm
 Weight: 400 Kg

If you are looking for another marine generator then you can browse the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	15.3
Continuous power single phase (KW)	13.9
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	115 / 230
Engine	Yanmar 4TNV88, 4 stroke
Engine rpm (rpm)	1500
Speed governor	Centrifugal, mechanical
Engine capacity (cm ³)	2190
Number cylinders	4
Cooling	Air
Inyección	Direct
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Consumption (L/h)	5.6 at 100% of the load
Acoustic pressure	52 dB(A) at 7 m
Length (mm)	1135
Width (mm)	631
Height (mm)	694
Dry weight (Kg)	400
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes

Product type	Generator
Voltage regulator	AVR
Engine manufacturer	Yanmar
