



MASE MARINER 2800 S SINGLE PHASE MARINE GENERATOR SILENCED 30KW

Reference: MARINER 2800 S

MASE MARINER 2800 S SILENCED SINGLE-PHASE MARINE GENERATOR 30 KW EPA

MASE MARINER2800S single phase silenced marine generator is equipped with a YANMAR 4TNNV98 diesel engine capable of delivering a maximum power of 30 KW at 1800 rpm.

The alternator of the generator is synchronous with 4 poles, self-regulated, self-excited, brushless, which in combination with the YANMAR engine can deliver a maximum power of 30 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like the home.

The MASE MARINER2800S allows easy access for maintenance of the lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER2800S is equipped with a soundproof cabin that makes it super silent, with a sound emission of 56dB(A) at a distance of 7 m. The painted aluminum soundproofing cabin is extremely lightweight and of very high resistance to external agents.

The MASE MARINER2800S has innovative features that provide boat builders and end users with extreme ease of installation, high efficiency, high performance and quiet operation, while ensuring a very low level of environmental impact.

TECHNICAL FEATURES MASE MARINER2800S

Phase Type: Single Phase
Maximum Power: 30 KW
Fuel: Diesel
Voltage: 120 - 240 V
Frequency: 60 Hz
Engine: YANMAR 4TNNV98, 4 Stroke
Emission Standard: Not Emitted
Mechanical Power: 56 Hp
Number of Cylinders: 4
Displacement: 3319 cc
Engine RPM: 1800 rpm
Fuel Consumption: 8.9 l/h
Sound pressure: 56 dB(A) @ 7 m
Alternator: Synchronous Brushless
Voltage regulator: AVR
Length: 1295mm
Width: 630 mm
Height: 810 mm
Weight: 595 Kg

If you are looking for another marine generator then you can browse the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	30
Continuous power single phase (KW)	28
Fuel	Diesel
Frequency (Hz)	60
Voltage (V)	120 / 240
Engine	Yanmar 4TNV98, 4 stroke
Engine rpm (rpm)	1800
Speed governor	Centrifugal, mechanical
Engine capacity (cm ³)	3319
Number cylinders	4
Oil capacity (L)	10.5
Cooling	Air
Inyección	Direct
Alternator	Synchronous, self-excited
Poles	4
Compression ratio	18 : 1
Lubrication	Forced
Consumption (L/h)	8.9 at 100% of the load
Acoustic pressure	56 dB(A) at 7 m
Length (mm)	1295
Width (mm)	630
Height (mm)	810
Dry weight (Kg)	595
Inverter	No
AVR	Yes

Compound	No
Silenced	Yes
Super silenced	Yes
