

## MASE FM 7.5 H

Reference: 001890



La linea di prodotti Mase marini è stata sviluppata per installazioni a bordo di imbarcazioni. I modelli IS ( Intercooler System), generatori diesel dalle caratteristiche innovative, assicurano ai costruttori di imbarcazioni e agli utilizzatori finali estrema facilità d'installazione, alta efficienza, elevate prestazioni e silenziosità, garantendo al tempo stesso un bassissimo livello di impatto ambientale.

L'immagine è puramente indicativa

### Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	4.6
Continuous power single phase (KW)	3.3
Maximum power single phase (KVA)	4.6
Continuous power single phase (KVA)	3.3
Maximum power three phase (KW)	8.75
Continuous power three phase (KW)	8.125
Maximum power three phase (KVA)	7
Continuous power three phase (KVA)	6.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A CE - 2 x 230V 16A 2P+T CE
Engine	Honda GX390, 4 stroke

Engine rpm (rpm)	3000
Ignition	Recoil
Starting system	Manual
Engine capacity (cm <sup>3</sup> )	389
Number cylinders	1
Cooling	Air
Alternator	Synchronous
Fuel tank capacity (L)	6.5
Consumption (L/h)	2.6 at 75% of the load
Running time (h)	2.5 at 75% of the load
Acoustic power	100 dB(A)
Acoustic pressure	75 dB(A) at 7 m
Length (mm)	725
Width (mm)	515
Height (mm)	585
Dry weight (Kg)	95
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	No
Engine manufacturer	Honda