



MASE FX 12001 GH GENERATOR 11 KVA SINGLE PHASE STAGE V AVR

Reference: 003408

MASE FX 12001 GH GENERATOR 11 KVA SINGLE PHASE STAGE V AVR

MASE FX 12001 GH is a single-phase generator, equipped with a Gasoline engine Honda GX630 **StageV**, it delivers a maximum power of 11KVA, complete with AVR voltage regulator.

MASE FX 12001 GH is equipped with a user friendly electric starter, thanks to which the ignition of the group is incredibly easy and safe. MASE FX 12001 GH provides reliable power for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

AVR VOLTAGE REGULATOR

The MASE FX 12001 GH generator is supplied complete with voltage regulator. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to the AVR there are fewer drops or peaks in current and this makes the use of the various connected devices safer, improving their performance and duration.

STAGEV EMISSIONS REGULATION

The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

Technical characteristics of MASE FX 12001 GH

Phase type: Single phase
Maximum power: 11 KVA / 8.8 KW
Continuous use power: 10 KVA / 8 KW
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Engine: Honda GX630
Engine revs: 3000 rpm
Emissions standard: Stage V
Voltage regulator: AVR
Starting: Electric
Tank capacity: 29 l
Consumption: 6 Lt / h at 75% of the load
Acoustic pressure: 73 dB (A) @ 7 m
Length: 940 mm

Width : 488 mm
 Height: 823 mm
 Weight: 148 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to MASE generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	8.8
Continuous power single phase (KW)	8
Maximum power single phase (KVA)	11
Continuous power single phase (KVA)	10
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A CEE - 1 x 230V 32A CEE
Engine	Honda GX630, 4 stroke, OHV
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm ³)	
Number cylinders	2
Cooling	Air
Alternator	Sincrono
Fuel tank capacity (L)	29
Consumption (L/h)	6 at 75% load
Running time (h)	4.83 at 75% of the load
Acoustic power	98 dB(A)
Acoustic pressure	73 dB(A) at 7 m
Length (mm)	940
Width (mm)	488
Height (mm)	823
Dry weight (Kg)	148
Silenced	No
Super silenced	No

ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Honda
