



## MASE SILENT 6000 B/A GENERATOR 3.6 KW SINGLE-PHASE STAGE V AVR

Reference: 003370

### MASE SILENT 6000 B/A SINGLE-PHASE GENERATOR 3.6 KW

MASE SILENT 6000 B/A is a single-phase generator equipped with a Honda GX270 OHV gasoline engine, capable of delivering a maximum power of 3.6 KW.

The MASE SILENT 6000 B/A single-phase generator provides reliable power for home, business and recreational environments, safely powering appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop with clear, intuitive controls. MASE SILENT 6000 B/A is equipped with a Honda GX270 OHV gasoline engine. They are very reliable engines that ensure efficient combustion and **low fuel consumption**, they also feature a protection system that causes the engine to stop if the oil level is too low.

MASE SILENT 6000 B/A are designed for stationary applications and to meet every need, these generators are characterized by reliability and quiet operation. The units include electric start-up and provision for operation with an automatic control unit. The MASE SILENT 6000 B/A are equipped with **10.5lt tank** with a large cap that is convenient to unscrew even with work gloves

MASE SILENT 6000 B/A has an all-steel construction and a large metal tank. The generator guarantees an efficient and silent operation thanks to the Honda GX270 OHV which allows to deliver a maximum power of 3.6 KW.

The generator is supplied with:

- Automatic stop for low oil level
- 12V built-in battery
- 1 single-phase socket CEE 230V - 16A
- Power output protections
- Differential circuit breaker
- Voltmeter
- Hour meter
- Fixed wheels and concealable handles for handling

#### TECHNICAL FEATURES MASE SILENT 6000 B/A

Maximum power Single-phase: 3.6 KW  
Continuous use power Single-phase: 3.2 KW  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50 Hz  
Motor: Honda GX270 OHV  
Engine speed: 3000 rpm  
Displacement: 270 cm<sup>3</sup>  
Cooling: Air

Start: Electric  
Fuel tank capacity: 10.5 l  
Consumption: 2.2 Lt/h at 75% load  
Acoustic power: 86 dB (61 dB at 7 m)  
Protection class: IP 23  
Length: 1059 mm  
Width: 670 mm  
Height: 740 mm  
Weight: 138 Kg

Are you looking for a power generator with different characteristics? [Here](#) you can find the full range of products from MASE or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.6
Continuous power single phase (KW)	3.2
Maximum power single phase (KVA)	3.6
Continuous power single phase (KVA)	3.2
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A CE
Engine	Honda GX270, 4 tempi, OHV, aspirato naturalmente
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	270
Number cylinders	1
Oil capacity (L)	1.1
Cooling	Air
Alternator	Sincrono, autoeccitato, autoregolato, senza spazzole
Poles	2
Fuel tank capacity (L)	10.5
Consumption (L/h)	1.9 at 75% of the load
Running time (h)	5.5 at 75% of the load
Acoustic power	89 dB(A)

Acoustic pressure	64 dB(A) at 7 m
Length (mm)	942
Width (mm)	588
Height (mm)	720
Dry weight (Kg)	125
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Honda