



GENSET MG4010DM

Reference: MG 4010 DM

GENSET MG4010DM SINGLE-PHASE VEHICLE GENERATOR 4KVA

The GENSET MG4010DM is a 4KVA single-phase vehicle generator powered by a Yanmar diesel engine with electric start. The GENSET MG4010DM generator is compact and easy to use, and thanks to its compact size and lightweight, it is a vehicle-mounted generator that is easy to install.

This GENSET MG4010DM generator is perfect for vehicle installation. The GENSET MG4010DM also has low fuel consumption: only 1 Lt/h at 75% load. The GENSET MG4010DM generator, thanks to the high quality and efficiency of its components, is ideal for vehicle mounting.

The GENSET MG4010DM 4KVA generator is equipped with a remote control panel consisting of a multifunction digital display for reading generator single-phase voltage, battery voltage, frequency, hour meter, and engine RPM.

The GENSET MG4010DM generator is equipped with an air cooling system that ensures long-lasting and reliable operation even in harsh conditions.

The GENSET MG4010DM 4KVA generator is part of the vehicle range, and thanks to its soundproof casing, it is super-silent, minimizing noise emissions.

Technical specifications of the GENSET MG4010DM generator:

Phase Type: Single-Phase Maximum
Single-Phase Power: 4 KVA / 3.2 KW
Engine: Yanmar L 70 V
Engine Speed: 3000 rpm
Emission Standard: StageV
No. of Cylinders: 1
Cooling: Air
Displacement: 320 cm³
Power: 6 hp (4.5 kWm)
Starting System: Electric
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Fuel Consumption at 75%: 1 Lt/h
Sound Pressure: 89 (64 dB at 7 m)
Length: 640 mm

Width: 500 mm
 Height: 500 mm
 Dry Weight: 120 kg

If you are looking for a product like the GENSET MG4010DM then you can browse the full range of GENSET's [vehicle generator](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.2
Maximum power single phase (KVA)	4
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Yanmar L70V, 4 stroke
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	320
Number cylinders	1
Cooling	Air
Alternator	Synchronous
Protection degree	IP23
Motor insulation class	H
Consumption (L/h)	1
Acoustic power	89 dB(A)
Acoustic pressure	64 dB(A) at 7 m
Length (mm)	640
Width (mm)	500
Height (mm)	500
Dry weight (Kg)	120
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	No

Engine manufacturer

Yanmar
