

GENSET MG 16 DM

Reference: MG16 DM



Generating Sets from 1 KVA to 2000 KVA with manual or automatic starting.

Thanks to such a wide range, GenSet is able to present specific solutions in the different fields of application of the genset both for continuous use and for emergency use in case of interruption of the main network.

All GenSet generating sets strictly comply with EC regulations on safety in use and control of polluting emissions.

The image is purely indicative

Technical Sheet

| | |
|------------------------------------|-----------------|
| Phase | Single phase |
| Maximum power single phase (KW) | 15.3 |
| Continuous power single phase (KW) | 13.9 |
| Fuel | Diesel |
| Voltage (V) | 230 |
| Engine | Yanmar L70N |
| Engine rpm (rpm) | 1500 |
| Starting system | Electric |
| Engine capacity (cm ³) | 2190 |
| Number cylinders | 4 |
| Cooling | Water |
| Alternator | Synchronous |
| Consumption (L/h) | 4.4 |
| Acoustic power | 87 dB(A) |
| Acoustic pressure | 62 dB(A) at 7 m |
| Length (mm) | 1570 |
| Width (mm) | 650 |
| Height (mm) | 810 |

| | |
|---------------------|--------|
| Dry weight (Kg) | 550 |
| Silenced | Yes |
| Super silenced | Yes |
| ATS Switch device | No ATS |
| Voltage regulator | AVR |
| Engine manufacturer | Yanmar |
