



TECNOGEN H 8000TE/A WITH SEPARATE AUTOMATIC PANEL

Reference: H 8000TE/A

TECNOGEN H 8000TE/A WITH SEPARATE AUTOMATIC PANEL

Generating sets available in both single-phase and three-phase versions, with powers from 2.3 to 21 kVA MAX, equipped with gasoline or diesel engines, air-cooled, 3000 rpm, with electric and / or manual starting with recoil . Compact, simplified and economical, they boast an excellent price / performance / size and weight ratio.

Easily transportable thanks to the reduced dimensions due to an essential set-up, they are suitable for all those who need an economic source of energy. assembled with first-rate components that guarantee absolute reliability. Thanks to the latest generation Honda engines, the petrol versions of the COMPACT line fall within the parameters of the noise directive 2000/14 / EC.

The image is purely indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	3
Maximum power single phase (KVA)	3.8
Maximum power three phase (KW)	6
Maximum power three phase (KVA)	7.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	HONDA GC160
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	389
Number cylinders	1

Cooling	Air
Fuel tank capacity (L)	6.5
Consumption (L/h)	1.9
Running time (h)	3.43
Acoustic power	96 dB(A)
Length (mm)	780
Width (mm)	520
Height (mm)	560
Dry weight (Kg)	85
Silenced	No
Super silenced	No
ATS Switch device	ATS Included
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Honda