



TECNOGEN H15000TELX

Reference: H 15000 TELX

Generating sets available in both single-phase and three-phase versions, with powers from 4.5 to 13.3 kVA MAX, equipped with gasoline or diesel engines, air-cooled, 3000 rpm, with electric and / or manual start with self-winding. Characterized by a particularly sophisticated design, they also stand out in terms of the set-up. In fact, they have a complete coverage of the upper part consisting of a sturdy sheet metal roof with central lifting point, a 20 Lt tank in polyethylene and an electrical panel positioned in a special protected compartment, separated from the motor / alternator unit and therefore exempt. from vibrations, equipped with hour meter and magnetothermic / differential switch. Thanks to their features and the latest generation Honda engines, which allow the petrol versions to fall within the parameters of the noise directive 2000/14 / EC, the LX series generator sets are the ideal solution for operators who need generators equipped with a professional set-up while remaining in the range of non-soundproofed machines.

The image is purely indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	3
Maximum power single phase (KVA)	3.8
Maximum power three phase (KW)	10.4
Maximum power three phase (KVA)	13
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	HONDA GC160
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	688
Number cylinders	2
Cooling	Air

Fuel tank capacity (L)	20
Consumption (L/h)	7
Running time (h)	2.8
Acoustic power	98 dB(A)
Length (mm)	990
Width (mm)	550
Height (mm)	670
Dry weight (Kg)	133
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	No
Engine manufacturer	Honda