

TECNOGEN H2700

Reference: H 8000 TSS - C



Technical Sheet

| Phase | Single phase / Three phase |
|------------------------------------|----------------------------|
| Maximum power single phase (KW) | 3 |
| Maximum power single phase (KVA) | 3.8 |
| Maximum power three phase (KW) | 6 |
| Maximum power three phase (KVA) | 7.5 |
| Fuel | Gasoline |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Engine | HONDA GC160 |
| Emissions Regulations | Stage 5 |
| Engine rpm (rpm) | 3000 |
| Starting system | Electric |
| Engine capacity (cm ³) | 389 |
| Number cylinders | 1 |
| Cooling | Air |
| Fuel tank capacity (L) | 15 |
| Consumption (L/h) | 1.9 |
| Running time (h) | 7.8 |
| Acoustic power | 88 dB(A) |
| Length (mm) | 1100 |
| Width (mm) | 540 |

| | |
|---------------------|--------------|
| Height (mm) | 650 |
| Dry weight (Kg) | 140 |
| Silenced | No |
| Super silenced | Yes |
| ATS Switch device | Optional ATS |
| Voltage regulator | No |
| Engine manufacturer | Honda |
