



## TECNOGEN LD13000TE

Reference: LD 13000 TE

Generating sets available in both single-phase and three-phase versions, with powers from 2.3 to 21 kVA MAX, equipped with gasoline or diesel engines, air-cooled, 3000 rpm, electric and/or manual starting with recoil starter. Compact, simplified and economical, they boast an excellent price/performance/size and weight ratio.

Easily transportable thanks to the reduced overall dimensions due to an essential equipment, they are suitable for all those who need an economic source of energy, however assembled with first-rate components that guarantee absolute reliability. The petrol versions of the COMPACT line, thanks to the latest generation Honda engines, fall within the parameters of the noise directive 2000/14/EC.

The image is purely indicative.

### Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	3
Maximum power single phase (KVA)	3.8
Maximum power three phase (KW)	10.6
Maximum power three phase (KVA)	13.3
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	HONDA GC160
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	954
Number cylinders	2
Cooling	Air
Fuel tank capacity (L)	7

Consumption (L/h)	3.3
Running time (h)	2.5
Length (mm)	920
Width (mm)	520
Height (mm)	660
Dry weight (Kg)	190
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	No
Engine manufacturer	Lombardini