



TECNOGEN SH160E

Reference: SH160E

TECNOGEN SH160E MOTORWELDER 3,8KVA

TECNOGEN SH160E is a motorwelder equipped with a Honda GX270 gasoline engine, capable of delivering a singlephase power of 3.8KVA.

TECNOGEN SH160E is a motorwelder with a welding current from 120 to 160A max., with a gasoline engine at 3600 rpm max. air-cooled, in an open frame complete with recoil starter.

TECNOGEN SH160E features a rugged frame to protect a powerful HONDA GX270 motor capable of delivering 5KVA singlephase power with a maximum load consumption of 2.4 L/h.

TECNOGEN SH160 is with electric start with 12V battery supplied with acid or manual with self-winding, with control panel QM115 composed of single-phase CEE socket 2P+T 16A, thermal protection, singlephase Schuko socket 2P+T 16A.

TECHNICAL FEATURES TECNOGEN SH160E

Soldering at 60%: 110
Maximum single-phase power: 3.8 KVA
Fuel: Gasoline
Voltage: 230V
Engine: Honda GX270
Boosting: Electric
Length: 920 mm
Width: 520 mm
Height: 660 mm
Weight: 83 Kg

Are you looking for a motorwelding with different technical characteristics? [Here](#) you can find the full range of TECNOGEN and other specialized brands.

The images are purely indicative.

Technical Sheet

Phase

Single phase

Maximum power single phase (KVA)	3.8
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	HONDA GX270
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm ³)	270
Number cylinders	1
Cooling	Air
Welding current (A)	180 al 35% - 170 al 60%
Fuel tank capacity (L)	6
Consumption (L/h)	
Running time (h)	4
Acoustic power	95 dB(A)
Length (mm)	920
Width (mm)	520
Height (mm)	660
Dry weight (Kg)	83
Inverter	No
AVR	No
Compound	No
Silenced	Yes
Super silenced	No