



AMA DTV DP 20 G.E. DIESEL TANK 2000L

Reference: 61000120

AMA DTV DP 20 G.E. DIESEL TANK 2000L
 CONTAINER - DIESEL TANK DISTRIBUTOR APPROVED M.I.

Double walled tank, vertical axis, made of carbon steel

EN 10025. The external protective tank has a containment capacity equal to 100% of the inner tank. The structure is supported by support skirt and bottom bars that allow movement with a forklift truck on empty.

THE DTV - DP is equipped with

- Manhole protection thermowell (size Ø 420 mm), complete with hinged and padlockable lid, with manhole on the inside flanged Ø 450 mm., equipped with :
 - Quick grip loading connection with ring nut, UNI 3" in aluminium homologous. M.I;
 - 90 % internal load relief valve, M.I. approved;
 - Float level indicator with indicator dial ;
 - Vacuum lifting eyebolt welded to the upper bottom;
 - Venting device 1" ½" with flame breaker end cap in brass;
 - AISI steel earthing connection;
 - Suction connection 2", positioned at a height from the bottom of
- Approximately 10 cm to safeguard the quality of the product avoiding the suction of sediment or water deposited on the bottom of the tank.
- Drainage 1", with closing cap ;positioned on tank bottom;
- External access ladder to the manhole;
- Visual leakage control system on cavity through visual warning light;
- Painting with bi-component bottom and dried water-based paint oven-baked after sheet metal washing treatment.

Technical Sheet

Fluid type	Diesel
Main body material	Carbon steel EN 10025
Internal diameter (mm)	1270
Outer diameter (mm)	1300
Fuel tank capacity (L)	2000
Height (mm)	1880
Dry weight (Kg)	425