



## HONDA Outboard BF 2.3 LCHU Long Shaft 1.7 kW 2.3 Hp 57 cm<sup>3</sup>

Reference: BF 2.3DH LCHU

### HONDA BF2,3 LCHU Outboard BF2,3 LCHU Shaft 57 cm 1.7 kW 2.3 Hp 57 cm<sup>3</sup>

Honda BF2,3 is an outboard engines, it is powerful enough to take you into coastal waters on an inflatable boat or dinghy. Lightweight to carry, it includes ergonomic handles and can be easily stored in the trunk of your car.

The Honda BF2,3 outboards are single-cylinder 4-stroke engines with a top valve. They are easy to start with a manual system that allows the engine to turn freely right away. The outboards have the most advanced technology that precisely controls the ignition phase, so when you start it, even when cold, it will start without hesitation. The air-cooled BF2,3 provides great maneuverability with 360° rotation and a built-in fuel-saving space tank. Easy to transport wherever you wish to go.

A centrifugal clutch allows the engine to idle without operating the propeller blades. When you want to start moving, just act on the throttle knob, the clutch engages and drives the propeller a bit like it does in an automatic transmission.

It's very important for a small boat to be nimble and able to change direction quickly. The small Honda BF2,3 has a fast turning action, which is perfect for reversing without changing gears. Just turn the rudder 180 degrees and the boat is able to move in reverse. You'll be able to maneuver around tight spots in a harbor with ease.

Once securely mounted to the boat, you'll find that these Honda engines are very light and easy to pull out of the water by tilting them. This way you avoid damaging the engine's propellers when moving through shallow water or on shore. You can quickly get moving again by acting on the spring system that allows you to lock the motor for safety.

These Honda outboards BF2,3 are the lightest in their class, so it's no wonder they're easy to pull out. They've been made easier to carry, with an ergonomic handle positioned at just the right balance point, allowing you to walk normally without effort.

The sleek design has been taken care of throughout, right down to the slim gearbox that reduces drag in the water while promoting fuel economy.

The knob gives a remarkably smooth feel and is equipped with a screw-clutch that allows it to be locked at various speeds, thus relaxing your hand.

Improving the quality of our lives means, above all, taking care of the environment in which we live. We cannot allow boat fuel to pollute the marine environment. That's why Honda has made outboards cleaner, quieter and more environmentally friendly with the introduction of the 4-stroke.

First, the aluminum housing is anodized using Honda's patented "double seal" process (1). Then a layer of epoxy primer is applied (2) before silver gloss paint (3). As additional UV protection, a clear resin (4) is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

### Technical characteristics Honda BF2,3 DH LCHU outboard:

Net Power (kW): 1.7  
 Net Power (Hp): 2.3  
 Displacement: 57 cm<sup>3</sup>  
 Shank length: Long  
 Dry weight (Kg): 14  
 Starting: Manual  
 Ignition system: Transient  
 Setup and engine lifting: Manual / Manual 4 positions  
 Transom height (mm): 571  
 Length (mm): 410  
 Width (mm): 280  
 Height (mm): 1100  
 Bore x stroke: 45 x 36 mm  
 Engine Brand: Honda  
 Engine Type: OHV, 4 stroke  
 Number of cylinders: 1  
 Speed of rotation at full throttle (rpm): 5000-6000  
 Cooling system: Air

Are you looking for an outboard with different characteristics? [HERE](#) you can find the whole range of Honda outboards and other specialized brands.

Images are indicative only.

## Technical Sheet

Fuel	Gasoline
Engine	OHV, 4 stroke
Ignition	Transistorized
Starting system	Manuale
Engine capacity (cm <sup>3</sup> )	57
Number cylinders	1
Cooling	Air
Bore x stroke (mm)	45 x 36
Reduction ratio	2.42
Rpm at full throttle (rpm)	5000 - 6000
Appearance and engine lifting	Manual / Manual 4 position
Transom height (mm)	571
Net power (kW)	1.7
Fuel tank capacity (L)	1.1
Length (mm)	410
Width (mm)	280
Height (mm)	1100
Dry weight (Kg)	14
Shaft Length	L

---

Controls

None

---