



HONDA Outboard BF 5 SHU Short Shaft 3.7 kW 5 Hp 127 cm³

Reference: BF 5AK2 SHU

HONDA BF 5 SHU Outboard Motor Short Shaft 3.7 kW 5 HP 127 cm³

The Honda BF5 SHU is an outboard motor powerful enough to take you to coastal waters on an inflatable boat or dinghy. Lightweight to transport, they include ergonomic handles and can easily be stored in the trunk of your car.

The Honda BF5 SHU outboard motors are 4-stroke, single-cylinder, top-valve engines. They are easy to start with a manual system that allows the engine to turn freely right away. The outboards feature the most advanced technology that precisely controls the ignition timing, so when you start it, even from cold, it will start without hesitation. The air-cooled BF5 SHU model provides great maneuverability with 360° rotation and an integrated fuel-saving space tank. Easy to carry wherever you want to go.

A centrifugal clutch allows the engine to idle without turning the propeller blades. When you want to start moving, simply twist the throttle, the clutch engages and drives the propeller much like an automatic transmission.

It's very important for a small boat to be agile and able to change direction quickly. The small Honda BF5 SHU has a quick-turning action, which is perfect for reversing without changing gear. Simply turn the rudder 180° and the boat can move in reverse. You'll be able to maneuver around tight spots in a harbor with ease.

These Honda BF5 SHU outboards are the lightest in their class, so it's no wonder they're easy to take out. They have been made easier to carry, with an ergonomic handle positioned at the right balance point, allowing you to walk normally without strain.

Improving the quality of our lives means above all taking care of the environment we live in. We cannot allow boat fuel to pollute the marine environment. For this reason Honda has made outboards cleaner, quieter and more environmentally friendly with the introduction of the 4-stroke.

First the aluminum housing is anodized using Honda's patented "double seal" process (1). Then a layer of epoxy primer is applied (2) before the silver gloss paint (3). For additional protection from UV rays, a clear resin is applied as a finish (4). For added safety, a sacrificial anode is applied to all waterproof connectors. Honda BF5 SHU Outboard Technical Specifications: Net Power (kW): 3.7
Net Power (Hp): 5

Displacement: 127 cm³

Shaft Length: Short

Dry Weight (Kg): 27.5

Starting: Recoil

Control Type: Tiller

Engine Trim and Tilt: Manual 5-Position

Transom Height (mm): 561

Length (mm): 524

Width (mm): 347

Height (mm): 1147

Bore x Stroke: 60 x 45 mm

Engine Brand: Honda
Engine Type: OHV, 4-stroke
Number of Cylinders: 1
Full Throttle Speed ??(rpm): 4500-5500
Cooling System: Water
Battery Charge Capacity (A): 6

Looking for an outboard with different features? [HERE](#) you can find the full range of Honda outboards and other specialized brands.

Technical Sheet

Fuel	Gasoline
Engine	OHV, 4 stroke
Starting system	Pull starter
Engine capacity (cm ³)	127
Number cylinders	1
Cooling	Water (with thermostat)
Bore x stroke (mm)	60 x 45
Reduction ratio	2.08
Rpm at full throttle (rpm)	4500 - 5500
Appearance and engine lifting	Manual / Manual 5 position
Transom height (mm)	445
Net power (kW)	3.7
Fuel tank capacity (L)	12 (Accessory on Request)
Height (mm)	1005
Dry weight (Kg)	27
Shaft Length	S
Controls	Tiller