

PRAMAC GBW10Y STAGE V APERTO CON QUADRO COMANDO AUTOMATICO

Reference: SH100TYAV02 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	7.47
Continuous power three phase (KW)	6.81
Maximum power three phase (KVA)	9.34
Continuous power three phase (KVA)	8.51
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE
Emissions Regulations	Stage 5
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	1116
Number cylinders	3
Cylinders' position	In line
Oil capacity (L)	3.5
Cooling	Water
Alternator	Linz E1S13SB , with brushes
Poles	4
Fuel tank capacity (L)	51
Consumption (L/h)	2 at 75% of the load / 2.6 at 100% of the load

Running time (h)	25.6 at 75% of the load / 19.2 at 100% of the load
Length (mm)	1600
Width (mm)	870
Height (mm)	875
Dry weight (Kg)	250
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	Compound
Engine manufacturer	Yanmar