

PRAMAC GBW15P APERTO CON QUADRO COMANDO MANUALE (MCP)

Reference: SH130TPAU00 /



The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.
 Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.
 Available in open or hooded version.

Images are purely indicative.

Technical Sheet

| | |
|------------------------------------|---|
| Phase | Three phase |
| Maximum power three phase (KW) | 11.28 |
| Continuous power three phase (KW) | 10.18 |
| Maximum power three phase (KVA) | 14.1 |
| Continuous power three phase (KVA) | 12.72 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Sockets configuration | 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO |
| Emissions Regulations | Stationary Use |
| Speed governor | Mechanical |
| Starting system | Electric |
| Engine capacity (cm ³) | 1496 |
| Number cylinders | 3 |
| Cylinders' position | In line |
| Oil capacity (L) | 6 |

| | |
|------------------------|--|
| Cooling | Water |
| Alternator | Linz E1S13MD, with brushes |
| Poles | 4 |
| Fuel tank capacity (L) | 51 |
| Consumption (L/h) | 2.7 at 75% of the load / 3.6 at 100% of the load |
| Running time (h) | 18.6 at 75% of the load / 14.2 at 100% of the load |
| Length (mm) | 1600 |
| Width (mm) | 870 |
| Height (mm) | 950 |
| Dry weight (Kg) | 390 |
| Silenced | No |
| Super silenced | No |
| Product type | Generator |
| ATS Switch device | No ATS |
| Voltage regulator | Compound |
| Engine manufacturer | Perkins |