

## PRAMAC GSL30D APERTO CON QUADRO COMANDO MANUALE (MCP)

Reference: SG290TDAT00 /



### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	25.55
Continuous power three phase (KW)	24.31
Maximum power three phase (KVA)	31.94
Continuous power three phase (KVA)	30.39
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Deutz AG F4L2011, naturally aspirated
Emissions Regulations	Stationary Use
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	3110
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	10
Cooling	Air
Alternator	Mecc Alte ECP28-VL/4, brushless
Poles	4
Fuel tank capacity (L)	91
Consumption (L/h)	5.7 at 75% of the load / 7.5 at 100% of the load

Running time (h)	15.9 at 75% of the load / 12.1 at 100% of the load
Length (mm)	1400
Width (mm)	750
Height (mm)	1700
Dry weight (Kg)	663
Inverter	No
AVR	Yes
Compound	No
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Deutz