

## PRAMAC GSA42D

Reference: SG400TDAY00 /



Motore Diesel. Raffreddamento ad aria. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	33.66
Continuous power three phase (KW)	32.78
Maximum power three phase (KVA)	42.08
Continuous power three phase (KVA)	40.98
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Deutz AG F4L912, naturally aspirated
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	3110
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	11
Cooling	Air
Alternator	Mecc Alte ECO/P32-3S/4, brushless
Poles	4
Fuel tank capacity (L)	91
Consumption (L/h)	7.3 at 75% of the load / 10 at 100% of the load

Running time (h)	12.5 at 75% of the load / 9.1 at 100% of the load
Length (mm)	1800
Width (mm)	750
Height (mm)	1710
Dry weight (Kg)	776
Inverter	No
AVR	Yes
Compound	No
Silenced	No
Super silenced	No