



NANNI QMS16M SILENCED MARINE GENERATOR 16.2KW

Reference: QMS 16M-S

NANNI QMS16M MARINE GENERATOR 16.2KW

NANNI QMS16M is a three-phase marine generator equipped with a Kubota 4-stroke engine with Diesel power supply capable of delivering a maximum power of 16.2KW.

The NANNI QMS16M is equipped with a Kubota base engine which has been used for years in marine and industrial applications all over the world.

The NANNI QMS16M generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures.

The cooling system allows the NANNI QMS16M to operate at an optimal temperature. In the case of closed-loop heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS16M is improved, resulting in low fuel consumption.

NANNI QMS16M is complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The NANNI QMS16M's alternator provides 13.9 KW of power in continuous operation and can produce up to 16.2 KW. Protection level IP23 (protection level available on request).

TECHNICAL FEATURES NANNI QMS16M

Maximum power Single-phase: 16.2 KW
Continuous use power Single-phase: 13.9 KW
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Engine: Kubota, 4-stroke
Start: Electric
Consumption: 4.8 Lt/h at full load
Length: 1130 mm
Width: 600 mm
Height: 700 mm
Weight: 378 Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	16.2
Continuous power single phase (KW)	13.9
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Kubota, 4 stroke
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	2197
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	7.5
Cooling	Water
Inyección	Indirect (E-TVCS)
Alternator	Electronic regulator
Bore x stroke (mm)	87 x 92.4
Consumption (L/h)	4.8 at 100% of the load
Length (mm)	1130
Width (mm)	600
Height (mm)	700
Dry weight (Kg)	378