



## HYUNDAI 35611 Submersible Electric Pump 750 W

Reference: 35611

Submersible electric pump for the movement of infiltration water, irrigation of small gardens, emptying of cellars, garages and basements, drainage of small construction sites and wells of wastewater.

It can be used in fixed or mobile installations.

Equipped with integrated float that determines the start when there is a situation of excessive water level.

Specifically for fresh water.

The main body of the pump is made of shock-resistant resin resistant to the oxidation typical of pumps made of metal material, increasing its durability over time.

### EQUIPMENT

- Float
- Power cable 10 m

Images and technical data are not binding.

### Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Pump type	Submersible Pump
Fluid type	Clean water
Maximum output capacity (Lt/min)	205
Power (W)	750
Main body material	Impact-resistant resin
Float	Yes
Thermal protection	Yes
Maximum use depth (m)	7
Maximum height (m)	8.5
Maximum flow (m <sup>3</sup> /h)	12.5
IP classification	IPX8

---

Diameter feed pipe	G1-1/2"
Power cable length (m)	10
Product dimensions (mm)	158 x 165 x 327
Package dimensions (mm)	220 x 160 x 360
Gross weight (Kg)	5
Outlet diameter thread type (mm/inches)	40 mm - 1" 1/2

---