



MARINE GENSET PAGURO18000 VTE Supersilenced Three Phase 18 kVA

Reference: AP18038050S0

MARINE GENSET PAGURO18000 VTE SUPERSILENCED 18 KVA

MARINE GENSET PAGURO18000 VTE three-phase 18 KVA marine genset, with a Lombardini engine powered by diesel at 3000 rpm and water-cooled with stainless steel water/air heat exchanger.

The noise emissions of 49 dB(A) of the VTE PAGURO marine genset are reduced to a minimum as it is water-cooled and has a double anti-vibration system, making it one of the quietest of its kind.

The PAGURO18000 marine genset with 3000 rpm motor is compact and space-saving and is suitable for use on medium-sized boats, excellent for powering your boat in complete peace of mind.

Paguro18000 generator set features:

Fuel: Diesel

Engine revs (rpm): 3000

Phase type: Single/three-phase

Three-phase continuous power (KVA): 18

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Lombardini LDW 1404

Starter: Electric

Silenced: Supersilenced 54 dB(A)

Cooling: Fresh water with heat exchanger

Dry weight (kg): 230

Length (mm): 970

Width (mm): 580

Height (mm): 650

Engine

The Lombardini diesel-powered engine makes the PAGURO18000 marine genset efficient and reliable. Designed with stainless steel water/air heat exchanger.

Alternator

The alternator is synchronous, brushless and with class H insulation. The AVR voltage regulator stabilises the voltage and makes the PAGURO18000 marine genset perfect for powering even the most sensitive electronics and devices that fear voltage and current fluctuations.

It is also air-cooled.

Included with the PAGURO18000 alternator is the battery charger for the dedicated 12 V / 8 A starter battery.

Soundproofing capsule and double anti-vibration system

The reinforced fibreglass capsule with composite layering and the high-density soundproofing material coating make this generator set one of the most silent compared to its competitors.

The capsule allows installation even in cramped spaces, thanks to its composition: two upper parts and one lower part. Finally, the dual anti-vibration system, with 4 soft inner mounts and 4 semi-elastic outer mounts, makes the PAGURO18000 stable even in less calm waters and silenced, so you can enjoy your navigation without further worries.

If you are looking for another kind of product, you can browse the entire catalogue of marine gensets click [HERE](#).

Non-binding images and technical data.

""

Technical Sheet

Phase	Single phase / Three phase
Continuous power three phase (KW)	16
Continuous power three phase (KVA)	18
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Lombardini LDW1404
Engine rpm (rpm)	3000
Starting system	Electric
Number cylinders	4
Cooling	Fresh water with heat exchanger
Alternator	Synchronous, brushless
Consumption (L/h)	0.35
Acoustic pressure	54 dB(A)
Length (mm)	970
Width (mm)	580
Height (mm)	650
Dry weight (Kg)	230
Silenced	Yes
Super silenced	Yes
Engine manufacturer	Lombardini