



VTE PAGURO 16500 Marine Generator Three Phase 16.5 kVA Supersilenced

Reference: AP16538050S0

PAGURO16500 MARINE GENSET VTE super-silenced 16.5 KVA

VTE PAGURO16500 three-phase 16.5 KVA marine genset VTE PAGURO16500, with Lombardini 1500 rpm diesel engine and fresh water cooling with stainless steel water/air heat exchanger.

Noise emissions of 51 dB(A) of the VTE PAGURO16500 marine genset are reduced to a minimum as it is built with freshwater cooling and a double anti-vibration system, making it one of the quietest in its category.

The three-phase PAGURO16500 marine genset with 1500 rpm motor is compact and space-saving and is suitable for use on various types of boats, excellent for powering your boat in complete peace of mind.

Technical characteristics:

Fuel: Diesel
Engine revs (rpm): 1500
Phase type: Single/three-phase
Three-phase continuous power (KVA): 16.5
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Lombardini LDW2004
Starter: Electric
Silenced: Supersilenced 51 dB(A)
Cooling: Fresh water cooling by heat exchanger
Dry weight (kg): 320
Length (mm): 1300
Width (mm): 660
Height (mm): 750

Engine

The Lombardini diesel-powered engine makes the PAGURO16500 marine genset efficient and reliable. Designed with fresh water cooling by heat exchanger.

Alternator

The alternator is synchronous, brushless and with class H insulation. The AVR voltage regulator stabilises the voltage and makes the PAGURO16500 marine genset perfect for powering even the most sensitive electronics and devices that fear voltage and current fluctuations.

It is also air-cooled.

Included with the PAGURO16500 alternator is the battery charger for the dedicated 12 V / 8 A starter battery.

Soundproofing capsule and double vibration damping system

The reinforced fibreglass capsule with composite layering and the high-density soundproofing material coating make this generator set one of the most silent compared to its competitors.

The capsule allows installation even in cramped spaces, thanks to its composition: two upper parts and one lower part. Finally, the dual anti-vibration system, internal with 4 soft mounts and external with 4 semi-elastic mounts, makes the PAGURO16500 stable even in less calm waters and silenced, so you can enjoy your navigation without further worries. Silence is the watchword for this genset!

If you are looking for a different kind of product, you can browse our entire catalogue of marine gensets click [HERE](#).
 Non-binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Continuous power three phase (KW)	14
Continuous power three phase (KVA)	16.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Lombardini LDW2004
Engine rpm (rpm)	1500
Starting system	Elettrico
Number cylinders	4
Cooling	Fresh water with heat exchanger
Alternator	Synchronous, brushless
Consumption (L/h)	0.35
Acoustic pressure	51 dB(A)
Length (mm)	1300
Width (mm)	660
Height (mm)	750
Dry weight (Kg)	320
Silenced	Yes
Super silenced	Yes
Engine manufacturer	LOMBARDINI