



PRAMAC LIFTER HAND PALLET TRUCK GS25S4 1150x525 DOUBLE ROLLER

Reference: TAB4100Y000

Maximize Efficiency with the PRAMAC LIFTER HAND PALLET TRUCK GS25S4

The PRAMAC LIFTER HAND PALLET TRUCK GS25S4 1150x525 DOUBLE ROLLER redefines efficiency and reliability in manual load management. This pedestrian-operated pallet truck, with its formidable 2500 Kg load capacity and unparalleled manual maneuverability, is the cornerstone of modern material control.

Elevating Material Handling Standards

Double Roller Design: Ensures smooth, stable movement for heavy loads, enhancing executional efficiency.

Ergonomic and Manual execution: Tailored for user control and comfort, facilitating ease in manual material handling tasks.

Pedestrian-Friendly execution: Features like an ergonomic handle make the PRAMAC LIFTER GS25S4 a standard in user-friendly manual pallet trucks.

Substantial Load Management: Capable of handling up to 2500 Kg, it's designed for the demands of bustling warehouses and manufacturing facilities.

Precision Lift and Transport: The 115 mm lift height and 1150x525 fork size are optimized for effective pallet handling, reducing physical strain.

Designed for Durability and Safety

The PRAMAC LIFTER GS Series, and particularly the PRAMAC LIFTER GS25S4 model, embodies practicality and safety. It is equipped with start and exit rollers for seamless operation and a more comfortable handle, reducing fatigue over long periods of use. The model's thoughtful design ensures it navigates narrow aisles and executes tight turns with ease, prioritizing operator safety and pallet security.

The inclusion of a maximum pressure valve prevents overloading, preserving the truck's structural integrity. Furthermore, its frame, treated with a high-temperature polyester powder varnish, stands up against wear and environmental damage, embodying PRAMAC's commitment to durability.

The PRAMAC LIFTER Advantage

Choosing the PRAMAC LIFTER GS25S4 is more than an operational decision; it's an investment in efficiency and safety. This pallet truck not only meets but exceeds the requirements of intensive manual handling, offering a blend of performance, durability, and ergonomic design unmatched in the market.

Discover how the PRAMAC LIFTER GS25S4 can transform your material control processes, making your operations safer, more efficient, and more productive.

[Learn about other similar products.](#)

The images are only indicative of the product.

Drive	Manual
Operator type	Pedestrian
Load capacity (Kg)	2500
Load centre distance (mm)	600
Load axle to end forks (mm)	932
Wheel base (mm)	1192
Service weight (Kg)	63
Axle load, laden rear (Kg)	1796
Axle load, laden front (Kg)	767
Axle load, unladen front (Kg)	42
Axle load, unladen rear (Kg)	21
Tyres: front wheels	POLY.I. / NYLON
Tyres: rear wheels	NYLON
Diameter steering wheels (mm)	200
Width steering wheels (mm)	55
Diameter load rollers (mm)	82
Width load rollers (mm)	60
Quantity rear wheels	4
Rear balancing axle	No
Tread front (mm)	155
Tread rear (mm)	375
Lift height (mm)	115
Height of tiller in drive position max (mm)	1160
Height lowered (mm)	85
Overall length (mm)	1550
Length to face of forks (mm)	400
Overall width (mm)	525
Thickness fork (mm)	55
Width fork (mm)	150
Length fork (mm)	1150
Distance between fork arms (mm)	525
Ground clearance at centre of wheelbase (mm)	30
Aisle width (mm)	1835
Turning radius (mm)	1367
Lifting speed laden (strokes)	13

Lifting speed unladen (strokes)	13
---------------------------------	----

Weigher	No
---------	----
