Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

CGM 25NG GAS METANO - APERTO CON CENTRALINA MANUALE

Reference: CGM 50NG COFANATO MANUALE /

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	44
Continuous power three phase (KW)	40
Maximum power three phase (KVA)	55
Continuous power three phase (KVA)	50
Fuel	Natural Gas
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	General Motors RMG 5700
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm^3)	5700
Number cylinders	8
Cooling	Water
Alternator	Marelli, brushless
Poles	4
Bore x stroke (mm)	101.6 x 91.4
Natural Gas consumption (m^3/h)	18.1 at 100% of the load
Acoustic pressure	67 dB(A) at 7 m
Length (mm)	2200

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Width (mm)	1000
Height (mm)	1800
Dry weight (Kg)	1300
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	General Motors