



PRAMAC LIFTER HAND PALLET TRUCK GS25S2 800x525 SINGLE ROLLER

Reference: TA50100Y000

GS series is a suitable practical solution meeting all the needs of manual handling.
The GS PRO pallet truck is equipped as a standard with a start and exit roller and a more ergonomic handle.

Maximum pressure valve

When the maximum load capacity is exceeded, oil pressure exceeds its maximum limit and the valve automatically locks the forks.
Thus possible structural damage is avoided.

Varnishing

Following an appropriate conditioning operation the frame is varnished with polyester powder at a temperature of 250° to guarantee maximum resistance to wear and atmospheric agents.

The images are purely indicative.

Technical Sheet

Drive	Manual
Operator type	Pedestrian
Load capacity (Kg)	2500
Load centre distance (mm)	400
Load axle to end forks (mm)	582
Wheel base (mm)	842
Service weight (Kg)	55
Axle load, laden rear (Kg)	1791
Axle load, laden front (Kg)	764
Axle load, unladen front (Kg)	39
Axle load, unladen rear (Kg)	16
Tyres: front wheels	POLY.I. / NYLON
Tyres: rear wheels	NYLON
Diameter steering wheels (mm)	200

Width steering wheels (mm)	55
Diameter load rollers (mm)	82
Width load rollers (mm)	82
Quantity rear wheels	2
Rear balancing axle	No
Tread front (mm)	155
Tread rear (mm)	375
Lift height (mm)	115
Height of tiller in drive position max (mm)	1160
Height lowered (mm)	85
Overall length (mm)	1200
Length to face of forks (mm)	400
Overall width (mm)	525
Thickness fork (mm)	55
Width fork (mm)	150
Length fork (mm)	800
Distance between fork arms (mm)	525
Ground clearance at centre of wheelbase (mm)	30
Aisle width (mm)	1435
Turning radius (mm)	1017
Lifting speed laden (strokes)	13
Lifting speed unladen (strokes)	13
Weigher	No