



## PRAMAC LIFTER HAND PALLET TRUCK GS25S4 1150x685 DOUBLE ROLLER

Reference: TEB45AVY100

GS series is a suitable practical solution meeting all the needs of manual handling.  
The GS PRO pallet truck is equipped as a standard with a start and exit roller and a more ergonomic handle.

### Maximum pressure valve

When the maximum load capacity is exceeded, oil pressure exceeds its maximum limit and the valve automatically locks the forks.  
Thus possible structural damage is avoided.

### Varnishing

Following an appropriate conditioning operation the frame is varnished with polyester powder at a temperature of 250° to guarantee maximum resistance to wear and atmospheric agents.

The images are purely indicative.

## Technical Sheet

|                               |            |
|-------------------------------|------------|
| Drive                         | Manual     |
| Operator type                 | Pedestrian |
| Load capacity (Kg)            | 2500       |
| Load centre distance (mm)     | 600        |
| Load axle to end forks (mm)   | 932        |
| Wheel base (mm)               | 1192       |
| Service weight (Kg)           | 68         |
| Axle load, laden rear (Kg)    | 1797       |
| Axle load, laden front (Kg)   | 771        |
| Axle load, unladen front (Kg) | 46         |
| Axle load, unladen rear (Kg)  | 22         |

|  |                 |
|--|-----------------|
| Tyres: front wheels                          | POLY.I. / NYLON |
| Tyres: rear wheels                           | NYLON           |
| Diameter steering wheels (mm)                | 200             |
| Width steering wheels (mm)                   | 55              |
| Diameter load rollers (mm)                   | 82              |
| Width load rollers (mm)                      | 60              |
| Quantity rear wheels                         | 4               |
| Rear balancing axle                          | No              |
| Tread front (mm)                             | 155             |
| Tread rear (mm)                              | 535             |
| Lift height (mm)                             | 115             |
| Height of tiller in drive position max (mm)  | 1160            |
| Height lowered (mm)                          | 85              |
| Overall length (mm)                          | 1550            |
| Length to face of forks (mm)                 | 400             |
| Overall width (mm)                           | 685             |
| Thickness fork (mm)                          | 55              |
| Width fork (mm)                              | 150             |
| Length fork (mm)                             | 1150            |
| Distance between fork arms (mm)              | 685             |
| Ground clearance at centre of wheelbase (mm) | 30              |
| Aisle width (mm)                             | 1835            |
| Turning radius (mm)                          | 1367            |
| Lifting speed laden (strokes)                | 13              |
| Lifting speed unladen (strokes)              | 13              |
| Weigher                                      | No              |