



BM2 HOT AIR GENERATOR GP 18M

Reference: 03GP102

BM2 HOT AIR GENERATOR GP 18M

BM2 GP18M is a manual start hot air generator powered by LPG, perfect for heating closed but ventilated rooms such as construction sites, greenhouses and farms.

BM2 GP18M is powered by high-pressure LPG, with an integrated, direct-burning burner. BM2 GP18M hot air generator is manufactured with manual ignition by piezoelectric. For their power supply they are usually connected to LPG cylinders, which makes them handy and very economical.

The hot air generator BM2 GP18M is supplied complete with:

- Built-in LPG burner
- Safety thermostat
- Control with thermocouple and gas valve
- Power supply cable with plug
- Manual ignition with piezo-electric system
- Complies with UNI EN 1596:2008

TECHNICAL FEATURES BM2 GP18M

Maximum heat output: 18.58 KW / 15975 kcal/h / 63400 BTU/h

Minimum heat output: 11.3 KW / 9715 kcal/h / 38560 BTU/h

Power supply: LPG

Maximum gas consumption: 1.213 Kg/h

Minimum gas consumption: 0.744 Kg/h

Gas pressure: 0.7 - 0.3 bar

Efficiency: 100 %

Air flow rate: 520 m³/h

Air temperature at 20°C: 35 °C

Electrical power: 50 W

Voltage: 230 V

Phase: Single phase

Frequency: 50 Hz

Width: 425 mm

Length: 180 mm

Height: 280 mm

Dry weight: 5.5 Kg

Are you looking for a hot air generator with different technical characteristics? [Here](#) you can find the full range of BM2 hot air generators or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Fuel	LPG
Frequency (Hz)	50
Voltage (V)	230
Max rated heat power	18.58 KW - 15975 Kcal/h - 63400 BTU/h
Min rated heat power	11.3 KW - 9715 Kcal/h - 38560 BTU/h
Max Gas consumption (Kg/h)	1.213
Min Gas consumption (Kg/h)	0.744
Gas pressure (bar)	0.7÷0.3
Heat efficiency (%)	100
Air flow (m ³ /h)	520
Air temperature at 20°C (°C)	35
Power consumption (W)	50
Length (mm)	425
Width (mm)	180
Height (mm)	280
Dry weight (Kg)	5.5