Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

HONDA EU22i Generatore 2.2 KW inverter

Reference: EU 22 IT

HONDA EU22i generator 2.2 KW supersilenced inverter

HONDA EU22i Current Generator part of Honda's portable range, is a 2.2 KW single-phase, supersilenced generator with inverter technology voltage regulator.
This current generator is perfect for both hobby and professional use, thanks to the reliable gasoline-powered Honda engine and all the top-quality components it is composed of.

Specifications HONDA EU22I:

Phase Type: Single Phase
Maximum power Single-phase (kW): 2.2
Single-phase continuous power (kW): 1.8
Single-phase maximum power (kVA): 2.75
Single-phase continuous power use (kVA): 2.25
Fuel: Petrol
Voltage (V): 230
Frequency (Hz): 50 Hz
Engine: Honda GXR120
Type: 4-stroke, OHV, 1 cylinder
Starter: Manual recoil starter
Autonomy: 3h 30
Consumption: 1.02 Lt/h
Length: 509 mm
Width: 290 mm
Height: 425 mm
Weight (Kg): 20.7
Inverter
Displacement (cm^3) 121

All the power with maximum comfort
HONDA EU22i Generator is among the quietest in its class as it is designed with sound-insulated linings and a unique exhaust system silencer.
In addition, HONDA EU22i Generator is designed with lightweight materials such as magnesium, plus its ergonomic design such as the comfortable handle make this portable generator HONDA EU22i extremely easy to lift and carry.

Inverter voltage regulator
The inverter technology voltage regulator guarantees you a constant, clean and uninterrupted power supply. This way, thanks to

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

the inverter voltage regulator, you can connect your sensitive devices (PCs, smartphones, home appliances, etc.) to your HONDA EU22i Generator safely and without burning them out.

Safety First
HONDA EU22i Generator , like all HONDA portable generators , is equipped with the unique load sensing device: the ECO-Throttle™. This device allows, as the load increases, to increase the generator's revolutions automatically, so you will always have the energy you need without straining the generator HONDA EU22i. This also gives you great fuel savings.

Another device found in all Honda portable gensets is Oil Alert™ technology, which will automatically turn off the contact if the oil is below the safe level.

Unity Makes Strength
HONDA EU22i Generator can be connected together by a parallel cable that doubles the power. Connected in this way, they can meet the needs of small facilities such as delivering power to ensure the operation of air conditioning in an RV. Two smaller gensets are easier to manage and transport than one large one, and once in place, they can be connected to increase power.

Flat car battery? No problem if you have a HONDA EU22i.

With the HONDA EU22i generator, you'll never be stranded because thanks to a convenient 12 VDC outlet this portable genrer allows you to recharge a car battery while providing the necessary power for something else. HONDA EU22i is an all-around power source.

Warranty
When you purchase the HONDA EU22i generator you take advantage of the exclusive benefit of a national or commercial warranty, as long as the service schedule is met.

If you need routine maintenance instead, you can contact us by clicking on the link https://www.manelservice.com/maintenance.

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service accepts no liability for any changes made by the manufacturer.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.2
Continuous power single phase (KW)	1.8
Maximum power single phase (KVA)	2.75
Continuous power single phase (KVA)	2.25
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V SCHUKO
Engine	Honda GXR120, 4 stroke, OHV
Engine rpm (rpm)	4000

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Ignition	Transistorized
Starting system	Recoil
Engine capacity (cm³)	121
Number cylinders	1
Oil capacity (L)	0.4
Cooling	Forced air
Alternator	Multipolar
Bore x stroke (mm)	60 x 43
Fuel tank capacity (L)	3.6
Consumption (L/h)	0.93
Running time (h)	3.83
Acoustic power	90 dB(A)
Acoustic pressure	72 dB(A)
Length (mm)	509
Width (mm)	290
Height (mm)	425
Dry weight (Kg)	20.7
Inverter	Yes
AVR	No
Compound	No
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Inverter
Engine manufacturer	Honda