



SINCRO GK2 LA Single Phase Synchronous AC Alternator 20 kVA Capacitor

Reference: GK2 LA J609b c25.4

SINCRO GK2 LA ALTERNATOR 25,0 KVA SINGLE PHASE

Alternator SINCRO GK2 LA single phase with a power of 25,0KVA, this unit has a Brushless operation equipped with capacitor voltage regulator.

The alternator is provided for operation at frequency 50 or 60 HZ, the possibility of working on these two frequencies makes it possible the application for any service voltage increasing its versatility, for the correct operation. SINCRO GK2 LA has been realized with the body entirely in steel, this makes the alternator very resistant and suitable for heavy duty use.

All components that make up the SINCRO GK2 LA alternator are subjected to a specific coating and/or impregnation process to safeguard the functionality of the generator and to protect critical parts under various conditions of use.

SINCRO GK2 LA is a brushless alternator, this feature together with the high efficiency of the regulator ensure a low level of interference with radio waves.

SINCRO alternators are all equipped with a voltage regulator, in the case of the GK2 LA capacitor model.

Select the alternator that meets the **technical specifications you require**, visit our [dedicated section](#) to find out how.

TECHNICAL FEATURES SINCRO GK2 LA

Phase Type: Single-phase
Maximum single-phase output: 20.0 KW
Maximum single-phase continuous output: 16.0 KW
Maximum single-phase output: 25.0 KVA
Maximum single-phase continuous output: 20.0 KVA
Frequency: 50-60 Hz
Voltage: 230 V
Protection class: IP23
Agent speed: 3000 rpm
Number of poles: 2
Weight: 111Kg
Brushless
Voltage regulator: Condenser
Type of alternator: constant speed

Looking for a product with different features? [Here](#) you can find the full range SINCRO and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Engine rpm (rpm)	3000
Poles	2
Single-phase power (KW)	20
Single-phase power (KVA)	20
Efficiency (%)	83
Protection degree	IP23
Dry weight (Kg)	103
Brushes	No
Type of alternator	Constant Speed
Voltage regulator	Capacitor