



## **HONDA HRD536HX Petrol Self-Propelled Hydrostatic Lawnmower 2.7 kW**

Reference: HRD 536K4 HX E

### **HONDA HRD536HX PETROL SELF-PROPELLED HYDROSTATIC LAWNMOWER 2.7KW**

HONDA HRD 536 HX hydrostatic transmission lawnmower with 53 cm width equipped with Roto-stop™. HONDA HRD 536 CTX lawnmower with its powerful "Pro" motors and 53 cm wide heavy-duty aluminum cutting plates is durable, reliable and suitable for professional use. HONDA HRD 536 CTX lawnmower can handle any situation. Demanding mowing operations on large lawns are easy and smooth thanks to this extremely robust mower that has look and reliability of a true professional.

Roto-Stop® function on HONDA HRD 536 CTX mower allows you to stop blade without turning off engine, which is ideal if you have to drive along a driveway or a gravel section. With other standard features such as the high airflow bag & double arm reinforcement (with handle attached to the cutting deck), it is not surprising that their name is HRD Professional.

#### **Durable cutting plates**

The cast aluminum cutting plates mounted on HONDA HRD 536 CTX lawnmower offer an excellent power-to-weight ratio and excellent corrosion resistance.

#### **Maximum control, minimum difficulty**

The hydrostatic control gives you maximum precision and continuous, uniform speed control.

#### **Roto-stop® blade stop system**

Roto-stop® system allows you to stop the blades quickly and safely without turning off motor. This feature of HONDA HRD 536 CTX lawnmower is ideal if you want to empty the grass catcher bag, remove debris or cross paths and driveways.

#### **Cast iron drive shaft**

The long life of HRD & HRH is guaranteed by the durable cast iron cylinder barrel and crankshaft.

#### **Perfect for demanding work**

Protected by a durable cast iron cutting deck and reinforced cutting deck handle, HRD & HRH are designed to adapt to the most demanding jobs.

#### **Technical Specifications HONDA HRD536HX Lawnmower:**

Engine: Honda GCV160, OHC, 4 strokes

Forward speed: 0-1.4 m/s  
 Material of cutting plate: Aluminum  
 Blade brake: Roto-stop®  
 Cutting position adjustment: 7  
 Grass collecting bag capacity: 83 Lt  
 Noise level: 98 dB(A)  
 Grass harvest time 100 m<sup>2</sup>: 07 min 31 sec  
 Time mulching grass 100 m<sup>2</sup>: 03 min 09 sec  
 Mulching system: Optional  
 Garden size: Large gardens (over 500 m<sup>2</sup>)  
 Length: 1575 mm  
 Width: 574 mm  
 Height: 1018 mm  
 Dry weight: 49.3 Kg  
 Cutting plate size: 53 cm  
 Cutting height: 14-76 mm

Are you considering another type of HONDA lawnmower? Discover the full range of [lawnmowers](#) to find the machine that best suits your needs.

## Technical Sheet

Fuel	Gasoline
Engine	Honda GCV160, OHC, 4-stroke
Engine rpm (rpm)	2800
Engine capacity (cm <sup>3</sup> )	163
Oil capacity (L)	0.65
Fuel tank capacity (L)	1.5
Length (mm)	1575
Width (mm)	574
Height (mm)	1018
Dry weight (Kg)	49.3
Self propelled	Yes
Cutter deck size (mm)	530
Grass bag capacity (Litres)	83
Lawn size suggested	Over 500 square meters
Mulching System	Optional
Driving speed (m/s)	0 - 1.4
Cutting Height Positions	7
Grass collection time per 100 m <sup>2</sup> turf (min:sec)	07:31
Time for mulching grass for 100 m <sup>2</sup> turf (min:sec)	03:09
Cutting height (mm)	14-76

---

Traction type	Hydrostatic
Product type	Lawnmower
Engine manufacturer	Honda

---