



CGM 10B

Reference: CGM10B /

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	8.8
Continuous power single phase (KW)	8
Maximum power single phase (KVA)	11
Continuous power single phase (KVA)	10
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	N.1 x 230V 63A 3P CEE / N.1 x 230V 16A 3P CEE
Engine	Briggs&Stratton
Engine rpm (rpm)	3000
Starting system	Manual
Engine capacity (cm ³)	480
Number cylinders	2
Oil capacity (L)	1.7
Cooling	Air
Alternator	Linz, brushless
Poles	2
Fuel tank capacity (L)	8.5
Consumption (L/h)	3.9 at 100% of the load
Running time (h)	3.8

Acoustic pressure	73 dB(A) at 7 m
-------------------	-----------------

Length (mm)	860
-------------	-----

Width (mm)	550
------------	-----

Height (mm)	650
-------------	-----

Dry weight (Kg)	97
-----------------	----

Silenced	No
----------	----

Super silenced	No
----------------	----

ATS Switch device	No ATS
-------------------	--------

Voltage regulator	Capacitor
-------------------	-----------

Engine manufacturer	Briggs&Stratton
---------------------	-----------------
