



## CGM 12.5DE - APERTO CON CENTRALINA MANUALE

Reference: CGM 12.5DE APERTO MANUALE /

### Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	11
Continuous power single phase (KW)	10
Maximum power single phase (KVA)	13.75
Continuous power single phase (KVA)	12.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	N.1 x 230V 63A 3P CEE / N.1 x 230V 16A 3P CEE
Engine	KOHLER 25LD 425/2
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	851
Number cylinders	2
Oil capacity (L)	1.7
Cooling	Air
Alternator	Linz, brushless
Poles	2
Protection degree	IP55
Bore x stroke (mm)	75 x 77.6
Fuel tank capacity (L)	4

Consumption (L/h)	2.8 at 75% of the load
Running time (h)	1.4
Acoustic pressure	77 dB(A) at 7 m
Length (mm)	900
Width (mm)	600
Height (mm)	750
Dry weight (Kg)	170
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	Capacitor
Engine manufacturer	Kohler