

## CGM 1250P - COFANATO CON CENTRALINA AUTOMATICA



Reference: CGM 1250P COFANATO AUTOMATICO

### Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	1100
Continuous power three phase (KW)	1000
Maximum power three phase (KVA)	1375
Continuous power three phase (KVA)	1250
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	PERKINS 403A-11G
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	45842
Number cylinders	12
Cylinders' position	V 60°
Cooling	Water
Alternator	Marelli, brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	160 x 190
Fuel tank capacity (L)	400

Consumption (L/h)	196
Running time (h)	2 al 75% del carico
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	12192
Width (mm)	2438
Height (mm)	2896
Dry weight (Kg)	11500
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Perkins