



## CGM 12.5DE - APERTO CON CENTRALINA AUTOMATICA

Reference: CGM 15DW COFANATO MANUALE /

### Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	13.2
Continuous power three phase (KW)	12
Maximum power three phase (KVA)	16.5
Continuous power three phase (KVA)	15
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE
Engine	Lombardini LDW1003
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	686
Number cylinders	3
Cylinders' position	In line
Cooling	Water
Alternator	With brushes
Poles	2
Protection degree	IP44
Fuel tank capacity (L)	50

Consumption (L/h)	3.8
Running time (h)	13.2
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	1600
Width (mm)	700
Height (mm)	1050
Dry weight (Kg)	350
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	Compound
Engine manufacturer	Lombardini