



TELWIN SUPERIOR 630 CE VRD 230-400V

Reference: 816032

MMA, TIG-LIFT in direct current (DC), multiprocess, inverter welding machine with microprocessor control, designed for welding cellulosic electrodes and coated electrodes such as aluminium, rutile, basic, stainless steel, cast iron with diameter up to 8 mm. Superior 630 CE VRD has the "gouging" function and makes it possible MIG-MAG/FLUX welding with optional feeder.

Features:

- Compact and light
- High welding current stability in spite of mains voltage fluctuations
- Immediate control of the welding droplets transfer
- Regulation of arc force and hot start according to the type of electrode in use
- Anti-stick device
- VRD device
- Storage on on-board E2PROM of the last 9 alarms
- Remote control connector
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Not binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Efficiency (%)	86
Protection degree	IP23
Maximum permissible current (A)	44 / 35
No-load voltage (V)	65 / 73
Regulation current (A)	10 - 450 / 10 - 600
Diameter electrodes (mm)	1.6 - 8
Type of welding current	DC
Type of welding	MMA / MIG
Current max (A)	400 / 500
Length (mm)	670

Width (mm)	310
Height (mm)	560
Voltage regulator	Inverter
Weight (Kg)	43
