



## TELWIN MOTOINVERTER 204 CE HONDA

Reference: 815793

### TELWIN MOTOINVERTER 204 CE MOTOR WELDING MACHINE 6,6KW

TELWIN MOTOINVERTER 204CE is a motor welder equipped with a Honda GX270 engine powered by gasoline, delivers a three-phase power of 6.6KW.

TELWIN MOTOINVERTER 204CE is a petrol engine driven welder with HONDA inverter technology engine with high frequency permanent magnet alternator for MMA and TIG-DC electrode welding with smear ignition.

TELWIN MOTOINVERTER 204CE allows incredible flexibility of use with a wide variety of electrodes: rutile, basic, cellulosic, stainless, cast iron, etc. It can also be used as a direct current (DC) generator for powering power tools such as drills, grinders, etc.

#### Features:

- 4-stroke gasoline engine with recoil start and air cooling
- Automatic block for no oil
- Motor overspeed protection
- Continuous adjustment of the welding current
- High stability of the current to variations in motor speed
- Arc force devices, hot start, anti-stick
- Welding-generator selector switch
- Thermostatic protection.

#### THE TECHNICAL CHARACTERISTICS TELWIN MOTOINVERTER 204CE

Phase Type: Single-Phase  
Maximum Power: 6.6KW  
Frequency: 50 Hz  
Voltage: 230 V  
Welding Current Type: DC  
Welding Type: MMA / TIG  
No-load Voltage: 112 V  
Current Adjustment: 5-190 A  
Maximum Current: 160 A  
Electrode Diameter: 1.6 - 4 mm  
Fuel: Gasoline

Motor: Honda GX270  
Start: Manual  
Length: 840 mm  
Width: 470 mm  
Height: 480 mm  
Weight: 58 Kg

Are you looking for a welding machine with different technical characteristics? [Here](#) you can find the whole range TELWIN or other specialized brands.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Engine	Honda GX270, 4 stroke
Engine rpm (rpm)	3400
Starting system	Manual
Engine capacity (cm <sup>3</sup> )	270
Cooling	Air
Power (KW)	6.6
Protection degree	IP23
No-load voltage (V)	112
Regulation current (A)	5 - 190
Diameter electrodes (mm)	1.6 - 4
Type of welding current	DC
Type of welding	MMA / MIG
Current max (A)	160
Fuel tank capacity (L)	6
Acoustic power	97 dB(A)
Length (mm)	840
Width (mm)	470
Height (mm)	480
Voltage regulator	Inverter
Weight (Kg)	58