



## TELWIN MOTOINVERTER 264DCE

Reference: 815980

### TELWIN MOTOINVERTER 264DCE MOTORWELDING 8,1KW

TELWIN MOTOINVERTER 264DCE is a motorwelder equipped with a Lombardini 15LD440 engine powered by gasoline, provides a three-phase power of 8.1KW.

TELWIN MOTOINVERTER 264DCE is a petrol driven welder with inverter technology with high frequency permanent magnet alternator for MMA and TIG-DC electrode welding with smear ignition.

TELWIN MOTOINVERTER 264DCE with inverter technology and high-frequency permanent magnet alternator for MMA and TIG-DC electrode welding with spark ignition.

TELWIN MOTOINVERTER 264DCE has flexibility of use with a wide variety of electrodes: rutile, basic, cellulosic, stainless, cast iron, etc. It can also be used as a direct current (DC) generator to power power tools such as drills, grinders, etc.

Features:

- Automatic block for lack of oil
- Motor overspeed protection
- Continuous adjustment of welding current
- High stability of the current to the variations of the engine revolutions
- Hot start and anti-stick devices
- Arc force adjustment
- Welder-generator selector
- Thermostatic protection.

#### TECHNICAL FEATURES TELWIN MOTOINVERTER 264DCE

Phase Type: Single-Phase

Power: 8.1 KW

Mechanical Power: 11 Hp

Frequency: 50 Hz

Voltage: 230 V

Welding Current Type: DC

Welding Type: MMA / TIG

No-load Voltage: 113 V

Current Adjustment: 5-230 A

Maximum Current: 200 A

Electrode Diameter: 1.6 - 5 mm

Fuel: Diesel  
Engine: Lombardini 15LD440  
Boosting: Electric  
Length: 1050 mm  
Width: 580 mm  
Height: 720 mm  
Weight: 107 Kg

Are you looking for a welding machine with different technical characteristics? [Here](#) you can find the whole range of TELWIN or other specialized brands.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Engine	Lombardini 15LD440
Engine rpm (rpm)	3500
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	442
Cooling	Air
Power (KW)	8.1
Protection degree	IP23
No-load voltage (V)	113
Regulation current (A)	5 - 230
Diameter electrodes (mm)	1.6 - 5
Type of welding current	DC
Type of welding	MMA / MIG
Current max (A)	200
Fuel tank capacity (L)	5
Acoustic power	98 dB(A)
Length (mm)	1050
Width (mm)	580
Height (mm)	720
Voltage regulator	Inverter
Weight (Kg)	107