



HONDA TRACKED CARRIER HP 500 BX

Reference: HP 500HK2 BX E1

HONDA HP500BX TRACKED TROLLEY

Honda tracked trolleys make your job easier: they make transporting heavy materials easier and safer. They also take a load off your shoulders by reducing workplace injuries.

New generation hard workers

Ideal for use by construction, agricultural and emergency services workers, Honda tracked trolleys are suitable for a range of heavy-duty moving tasks. Equipped with the renowned 4-stroke engine, they are robust and efficient, capable of getting the job done.

Stay on track

On gravel, over rough terrain and even up stairs, the unique track tread on these trolleys provides incredible traction. They stand out for their great maneuverability with a rotation radius of 71 cm, furthermore the tread minimizes damage to the ground, an important aspect when working on lawns and gardens.

Technical Features HONDA HP500BX:

Load capacity on flat surfaces: 500 kg
Load capacity on slopes: 350 kg
Maximum load height - flat surface: 900 mm
Maximum forward speed: 4.3 km/h
Maximum reverse speed: 3.6 km/h
Maximum forward inclination: 15 degrees
Maximum backward inclination: 15 degrees
Platform length: 1200 mm
Platform width: 560 mm
Platform height: 200 mm

Are you looking for a product similar to the HP500BX but with different features? [CLICK HERE](#) to discover our full range.

Technical Sheet

Engine	Honda GXV160
Fuel tank capacity (L)	3.1

Acoustic power	99 dB(A)
Length (mm)	2140
Width (mm)	650
Height (mm)	1100
Capacità di carico in pendenza (Kg)	350
Altezza massima del carico-superficie piana (mm)	900
Velocità massima avanti (Km/h)	4.3
Velocità massima retromarcia (Km/h)	3.6
Inclinazione massima avanti	15°
Inclinazione massima indietro	15°
Lunghezza pianale (mm)	1200
Larghezza pianale (mm)	560
Altezza pianale (mm)	200