



## GENMAC DUPLEX G15YO Generating set 15 KVA 13 KW Open Automatic

Reference: G15YO

Open generator with the following structural characteristics:

Frame:

- Made of high quality steel UNI S235 JR with welded base
- Highly resistant vibration dampers between engine, alternator and crankcase
- Tank with drain for emptying
- Dedicated cable entry area for load connection
- Fuel loading niche
- Feet and four lifting rings fixed to the base

Framework:

- Metal square, with rear closing case
- Dedicated cable entry area for load connection

All machines and components are tested in prototyping, construction and production. A special control procedure during the various stages of production ensures long life and reliability.

QFIA-4520

Protective flap

Thermal-magnetic circuit breaker

Automatic Control Unit DSE4520

- Voltmeter, Frequency Meter, Ammeter
- Reading Generator power (kW, kV Ar, kV A & pf)
- Hour counter
- Fuel tool
- Overload protection (kW & kV Ar)
- Low oil pressure protection
- High refrigerant temperature protection
- Low fuel level protection
- Alternator battery charger failure
- Overrunning protections

Emergency Stop button

Terminal block for connection Automatic Framework

Battery Charger

On/off switch

Non-binding images and technical information.

**Technical Sheet**

Phase	Three phase
Maximum power three phase (KW)	12
Continuous power three phase (KW)	11
Maximum power three phase (KVA)	15
Continuous power three phase (KVA)	13
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	3TNV88-GMG
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	1640
Number cylinders	3
Oil capacity (L)	6.7
Cooling	Coolant Liquid
Poles	4
Tank capacity (L)	100
Current (A)	21
Consumption (L/h)	2.7 at 75% of the load
Running time (h)	37
Length (mm)	1400
Width (mm)	660
Height (mm)	1360
Dry weight (Kg)	390
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Yanmar