



MOSA GE 40 VSX EAS SECOND-HAND AVR+COMPOUND

Reference: USATO1

Super silenzioso. Motore Diesel. Protezione motore EP5. Alternatore sincrono trifase. Regolazione elettronica della tensione. Regolazione combinata AVR + COMPOUND della tensione. Interruttore differenziale. Interruttore magnetotermico. Pulsante d'emergenza. Predisposto per uso con Quadro automatico. Secondo direttive CE per rumore e sicurezza.

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	10.8
Continuous power single phase (KVA)	13.8
Maximum power three phase (KW)	32
Continuous power three phase (KW)	28.8
Maximum power three phase (KVA)	40
Continuous power three phase (KVA)	36
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 63A 3P+N+T CEE - 1 x 230V 16A 2P+T SCHUKO
Engine	VM MOTORI SUN 3105 TE2, 4 stroke turbocharged
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	2987
Number cylinders	3
Cooling	Air

Inyección	Direct
Alternator	Sincrono trifase, autoeccitato, autoregolato, senza spazzole
Fuel tank capacity (L)	68
Consumption (L/h)	7.1 at 75% of the load
Running time (h)	9.5 at 75% of the load
Acoustic power	91 dB(A)
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	1940
Width (mm)	850
Height (mm)	1080
Dry weight (Kg)	935
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR+Compound
Engine manufacturer	VM MOTORI