



MOSA GE 45 YSX EAS AVR+COMPOUND SECOND-HAND

Reference: USATO2

Super silenzioso. Motore Diesel. Regolatore elettronico di giri. Protezione motore EP6. Alternatore sincrono trifase. Regolazione combinata AVR + Compound della tensione. Terminale d'uscita a barre di rame. Interruttore differenziale. Interruttore magnetotermico. Pulsante d'emergenza. Predisposto per uso con quadro automatico. Secondo direttive CE per rumore e sicurezza

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	12.4
Continuous power single phase (KVA)	15.5
Maximum power three phase (KW)	36.8
Continuous power three phase (KW)	33.6
Maximum power three phase (KVA)	46
Continuous power three phase (KVA)	42
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 63A 3P+N+T CEE - 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T SCHUKO
Engine	Yanmar 4TNV98T, 4 stroke turbocharged
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	3319
Number cylinders	4
Cooling	Water

Inyección	Direct
Alternator	Sincrono trifase, autoeccitato, autoregolato, senza spazzole
Fuel tank capacity (L)	100
Consumption (L/h)	7.4 at 75% of the load
Running time (h)	13.5 at 75% of the load
Acoustic power	90 dB(A)
Acoustic pressure	65 dB(A) at 7 m
Length (mm)	2050
Width (mm)	900
Height (mm)	1420
Dry weight (Kg)	1020
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR+Compound
Engine manufacturer	Yanmar