



MARINE GENERATOR KOHLER 16EKOZD SINGLE-PHASE 15KVA 60Hz EPA

Reference: KOHLER 16 EKOZD 60hz

Super-silenced single-phase KOHLER 16EKOZD marine generator 15 KVA AVR

Kohler 16EKOZD Marine generator single phase 15 KVA with 1800 rpm motor EPA certified. The KOHLER 16EKOZD single-phase marine generator is built with a soundproof enclosure that makes it **supersilenced**. The KOHLER 16EKOZD single-phase marine generator is built with a 4-cylinder, 4-cycle Kohler diesel-powered engine, closed cooling system with heat exchanger. The alternator of the single-phase KOHLER 16EKOZD marine generator is brushless with **AVR** voltage regulator and water-cooled.

Features of the KOHLER 16EKOZD marine generator

- Class H insulation
- Multi-voltage adjustability
- Voltage adjustment of 1.0%.
- Radio suppression

Engine features of the KOHLER 16EKOZD marine generator

- Diesel
- Environmental Protection Agency (EPA) certified for compliance with Tier III marine auxiliary standards
- Four cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Electric fuel lift pump
- Lifting eyelet
- Low oil pressure shutdown
- High temperature engine shutdown
- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

TECHNICAL FEATURES KOHLER 16EKOZD

Phase Type: Single-Phase
Maximum Single-Phase Power: 15 KW
Fuel: Diesel
Frequency: 60 Hz

Voltage: 120/240 V
Motor: Kohler
Emissions Regulation: EPA
Engine RPM: 1800 rpm
Length: 1064 mm
Width: 652.5 mm
Height: 711 mm
Dry Weight: 393 Kg

Other marine generators such as the KOHLER 16EKOZD can be found by browsing the entire catalog of [marine generators](#).

Pictures and technical data are not binding.

Technical Sheet

| | |
|-------------------------------------|-------------------------|
| Phase | Single phase |
| Continuous power single phase (KW) | 15 |
| Continuous power single phase (KVA) | 15 |
| Fuel | Diesel |
| Frequency (Hz) | 60 |
| Engine | Kohler |
| Emissions Regulations | EPA |
| Engine rpm (rpm) | 1800 |
| Speed governor | Mechanical |
| Engine capacity (cm ³) | 1900 |
| Number cylinders | 3 |
| Cooling | Water |
| Bore x stroke (mm) | 88 x 102 |
| Compression ratio | 17 : 1 |
| Motor insulation class | H |
| Consumption (L/h) | 3.51 at 75% of the load |
| Length (mm) | 1064 |
| Width (mm) | 652.5 |
| Height (mm) | 711 |
| Dry weight (Kg) | 393 |
| Silenced | Yes |
| Super silenced | Yes |
| Type of combustion | Direct |
| Voltage regulator | AVR |

Engine manufacturer

Kohler